

EAST - [10816931.wsp:1]

File View Edit Tools Window Help

Active

- L1: (169030) "455"/\$.cls. "370"/\$.cls.
- L3: (169030) "455"/\$.cls. or "370"/\$.cls.
- L4: (11053) 1 and "packet switched"
- L5: (2420) 4 and (handover hand\$loff handoff "hand off")
- L6: (16) 5 and "logical link layer"
- L7: (14) 6 and frame
- L8: (1) 7 and "ciphering parameter"
- L9: (14) 7 and node
- L10: (7) 9 and GPRS
- L11: (3) 10 and state
- L12: (10) 5 and "ciphering parameter"
- L13: (6) 5 and "ciphering parameter"
- L14: (78) 5 and "second node"
- L15: (0) 14 and "logical link layer"
- L16: (1) 6 and "ciphering parameter"
- L17: (1) 6 and "ciphering"
- L18: (10) 5 and "ciphering parameter"

Failed

Search List Browse Quote Clear

DBs US-PGPUB: USPAT: EPO

Default operator: OR

Plurals

Highlight all hit terms initially

5 and "ciphering parameter"

BRS form IS&P form Image Text HTML

	U	I	Document ID	Issue Date	Pages	Title	Current OR	Current	Ret	Inventor	
1	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 7065340 B1	20060620	13	Arranging authentication and ciphering in mobile communi	455/410	380/270; 380/273;		Einola: Heikki et al.	F
2	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 6535979 B1	20030318	16	Method of ciphering data transmission, and cellular radi	713/163	370/343; 370/476;		Vialen: Jukka et al.	F
3	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 6469992 B1	20021022	30	Intelligent packet retransmission scheme	370/329	370/349; 370/389;		Schieder: Andreas	F
4	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 6466556 B1	20021015	15	Method of accomplishing handover of packet data flows	370/331	370/390; 455/442;		Boudreaux: Paul H.	F

Hits Details HTML

Ready

NUM



- ☐ BRS: "455"/\$.ccls or "370"/\$.cc
- ☐ BRS: ls.

☒ ☒ Active

☒ ☒ Active


- L3: (169030) "455"/\$.ecls. or "370"/\$.ecls.
- L4: (11053) 1 and "packet switched"
- L5: (2420) 4 and (handover hand\$1 off handoff "hand off")
- L6: (16) 5 and "logical link layer"
- L7: (14) 6 and frame
- L8: (1) 7 and "ciphering parameter"
- L9: (14) 7 and node
- L10: (7) 9 and GPRS
- L11: (3) 10 and state
- L12: (10) 5 and "ciphering parameter"
- L13: (6) 5 and "ciphering parameter"

☒ Failed

Search	List	Browse	Queue	Clear
DBs	USPAT	<input checked="" type="checkbox"/> Plurals - <input checked="" type="checkbox"/> Highlight all hit terms initially		
Default operator:		OR		

5 and "ciphering parameter"

[illegible]



3 BRS: "455"/\$.ccls or "370"/\$.cc
3 BRS: ls.

☒ Active

- L1: (169030) "455"/\$.cccls. "370"/\$.cccls.
- L3: (169030) "455"/\$.cccls. or "370"/\$.cccls.
- L4: (11053) 1 and "packet switched"
- L5: (2420) 4 and (handover hand\$1off handoff "hand off")
- L6: (16) 5 and "logical link layer"
- L7: (14) 6 and frame
- L8: (1) 7 and "ciphering parameter"
- L9: (14) 7 and node
- L10: (7) 9 and GPRS
- L11: (3) 10 and state

 Saved

Favorites

Search

DBs: ☒ Plurals

Default operator: ☒ Highlight all hit terms initially

10 and state

 BRS form
  IS&R form
  Image
  Text
  HTML

	U	1	Document ID	Issue Date	Pages	Title	Current OR	Current	Ret	Inventor	S
1	<input type="checkbox"/>	<input type="checkbox"/>	US 20050185619 A1	20050825	28	Method for performing packet switched handover in a mobil	370/331	455/436		Niemela, Tuomas et al.	R
2	<input type="checkbox"/>	<input type="checkbox"/>	US 20010030965 A1	20011018	14	Data packet numbering in packet-switched data transmis	370/394	370/466		Tourunen, Ari et al.	R
3	<input type="checkbox"/>	<input type="checkbox"/>	US 7167475 B2	20070123	16	Data packet numbering in packet-switched data transmis	370/394	370/328; 370/338;		Tourunen, Ari et al.	R

Hits Details HTML